


FRESA TALLADO DE ENGRANAJES

HSS

- Ejecución: HSS.

Nº FRESA	1	2	3	4	5	6	7	8
Nº DIENTES A TALLAR	12-13	14-16	17-20	21-25	26-34	35-54	55-134	135-∞



144061

Unid:mm

HSS

MODULAR


Tol D
js16Tol D₁
H7PRESIÓN
β20°

CÓDIGO	Mod.	D	D1	Nº CORTES	CÓDIGO	Mod.	D	D1	Nº CORTES
0050	0,50	40	16	12	0355	3,55	75	27	10
0075	0,75	40	16	12	0375	3,75	80	27	10
0100	1,00	50	16	12	0400	4,00	80	27	10
0125	1,25	50	16	12	0450	4,50	85	27	10
0150	1,50	60	22	12	0500	5,00	90	32	10
0175	1,75	60	22	12	0550	5,50	95	32	10
0200	2,00	60	22	12	0600	6,00	100	32	10
0225	2,25	60	22	10	0650	6,50	105	32	10
0250	2,50	65	22	10	0700	7,00	105	32	10
0275	2,75	70	27	10	0800	8,00	110	32	9
0300	3,00	70	27	10	0900	9,00	115	32	9
0325	3,25	75	27	10	1000	10,00	120	32	9

FRESA MADRE TALLADO DE ENGRANAJES

HSS

- Ejecución: HSS, DIN 858.



144065

Unid:mm

HSS

DIN
858

MODULAR

Tol
H6PRESIÓN
β20°

TIN

CÓDIGO	Mod.	D	D1	L	Nº CORTES	CÓDIGO	Mod.	D	D1	L	Nº CORTES
0050	0,50	45	22	35	12	0300	3,00	70	27	70	10
0075	0,75	45	22	45	12	0325	3,25	75	27	70	9
0100	1,00	50	22	50	12	0350	3,50	75	27	75	9
0125	1,25	50	22	50	12	0375	3,75	80	27	75	9
0150	1,50	55	22	55	12	0400	4,00	80	27	80	9
0175	1,75	55	22	55	10	0450	4,50	85	27	85	9
0200	2,00	60	22	60	10	0500	5,00	95	27	90	9
0225	2,25	60	22	60	10	0550	5,50	100	32	95	9
0250	2,50	65	22	65	10	0600	6,00	105	32	100	9
0275	2,75	65	22	65	10	1000	10,00	140	32	160	8