


TERRAJAS PARA ROSCAR A MANO

M


- **Ejecución:** HSS, DIN 223.
- Diámetro previo de la varilla para el roscado.



151101

Unid:mm

HSS

DIN
223Tol
6g

CÓDIGO	ROSCA-PASO	D	L	Ø
0102	M 1 x 0,25	16	5	0,96
0204	M 2 x 0,40	16	5	1,95
0254	M 2,5 x 0,45	20	5	2,92
0305	M 3 x 0,50	20	5	2,92
0356	M 3,5 x 0,60	25	9	3,41
0407	M 4 x 0,70	20	5	3,90
0457	M 4,5 x 0,75	20	7	4,40
0508	M 5 x 0,80	20	7	4,90
0610	M 6 x 1,00	20	7	5,88
0710	M 7 x 1,00	25	9	6,88
0812	M 8 x 1,25	25	9	7,86
0912	M 9 x 1,25	25	9	8,86
1015	M 10 x 1,50	30	11	9,85
1115	M 11 x 1,50	30	11	10,85
1217	M 12 x 1,75	38	14	11,83
1317	M 13 x 1,75	38	14	12,83
1420	M 14 x 2,00	38	14	13,82
1520	M 15 x 2,00	45	14	14,82
1620	M 16 x 2,00	45	18	15,82
1825	M 18 x 2,50	45	18	17,79
2025	M 20 x 2,50	45	18	19,79
2225	M 22 x 2,50	55	22	21,79
2430	M 24 x 3,00	55	22	23,76
2730	M 27 x 3,00	65	25	26,76
3035	M 30 x 3,50	65	25	29,73
3335	M 33 x 3,50	65	25	32,73
3640	M 36 x 4,00	65	25	35,70
3940	M 39 x 4,00	75	30	38,70
4245	M 42 x 4,50	75	30	41,68
4545	M 45 x 4,50	90	36	44,68
4850	M 48 x 5,00	90	36	47,66
5250	M 52 x 5,00	90	36	51,66

Aceros Carbono	Aceros Aleados	Aceros Preendurecidos	Aceros Endurecidos		Fundición	Aluminio	Inoxidable	Titanio	Cobre	Bronce	CFRP
~HB225 ⊙	HB225 ~325	HRC30~45	HRC 45 ~55	HRC 55~							