


TERRAJAS PARA ROSCAR A MANO

BSW


- **Ejecución:** HSS, DIN 223.
- Diámetro previo de la varilla para el roscado.



151161

Unid:mm

HSS

DIN
223

CÓDIGO	ROSCA-HILOS	D	L	Ø
0260	W 1/16-60h	16	5	1,51
0448	W 3/32-48h	20	5	2,26
0640	W 1/8-40h	25	9	3,12
0832	W 5/32-32h	25	9	3,82
1024	W 3/16-24h	25	9	4,69
1224	W 7/32-24h	25	9	5,39
1420	W 1/4-20h	25	9	6,16
1618	W 5/16-18h	25	9	7,76
1816	W 3/8-16h	38	10	9,30
2014	W 7/16-14h	38	10	10,98
2212	W 1/2-12h	38	14	12,43
2412	W 9/16-12h	38	14	13,92
2611	W 5/8-11h	45	18	15,62
2811	W 11/16-11h	45	18	17,20
3010	W 3/4-10h	45	18	18,76
3209	W 7/8-9h	55	22	21,89
3408	W 1-8h	55	22	25,08
3607	W 1.1/8-7h	65	25	28,21
3804	W 1.1/4-7h	65	25	31,35
4006	W 1.3/8-6h	65	25	34,48
4206	W 1.1/2-6h	75	30	37,67
4405	W 1.5/8-5h	75	30	41,11
4605	W 1.3/4-5h	90	36	43,94
4804	W 1.7/8-4,5h	90	36	47,75
5004	W 2-4,5h	90	36	50,26

Aceros Carbono	Aceros Aleados	Aceros Preendurecidos	Aceros Endurecidos		Fundición	Aluminio	Inoxidable	Titanio	Cobre	Bronce	CFRP
~HB225 ◎	HB225 ~325	HRc30~45	HRc 45 ~55	HRc 55~							

- Consulten plazo de entrega.

◎ : Excelente

○ : Bueno