



MACHOS PARA ROSCAR A MAQUINA AGUJEROS PASANTES

S/NC

- **Ejecución:** HSSE PM, DIN 371 - DIN 376, con corte inicial forma B.
- Superficie con recubrimiento TICN.
- **Aplicación:** especialmente aconsejable para maquinas CNC.




151299

Unid:mm

HSSE
PM

DIN
371-376



B
4-5P

Tol
6HX

TICN



CÓDIGO	ROSCA-PASO	D1	L	L1	☐	TALADRADO		
0305	M 3 x 0,50	3,5	5	56	2,7	2,50	*	
0407	M 4 x 0,70	4,5	7	63	3,4	3,30	*	
0508	M 5 x 0,80	6,0	8	70	4,9	4,20	*	
0610	M 6 x 1,00	6,0	10	80	4,9	5,00	*	
0812	M 8 x 1,25	8,0	13	90	6,2	6,75	*	
1015	M 10 x 1,50	10,0	15	100	8,0	8,50	*	

151300

1217	M 12 x 1,75	9,0	18	110	7,0	10,20		*
1420	M 14 x 2,00	11,0	20	110	9,0	12,00		*
1620	M 16 X 2,00	12,0	20	110	9,0	14,00		*

Aceros Carbono	Aceros Aleados	Aceros Preendurecidos	Aceros Endurecidos		Fundición	Aluminio	Inoxidable	Titanio	Cobre	Bronce	CFRP
~HB225 ◎	HB225 ~325 ◎	HRc30~45	HRc 45 ~55	HRc 55~							

◎ : Excelente

○ : Bueno