

## JUEGO DE MACHOS PARA ROSCAR A MANO

BA


- Ejecución: HSS, DIN 352.
- Juego de 3 machos.



151077

Unid: mm

HSS

DIN  
352

| CÓDIGO | ROSCA-PASO  | D   | L  | L1 | ☑   | TALADRADO |
|--------|-------------|-----|----|----|-----|-----------|
| 0000   | BA-0 x 1,00 | 6,0 | 18 | 50 | 4,9 | 5,10      |
| 0100   | BA-1 x 0,90 | 5,3 | 18 | 50 | 4,9 | 4,50      |
| 0200   | BA-2 x 0,81 | 4,7 | 17 | 50 | 4,9 | 4,00      |
| 0300   | BA-3 x 0,73 | 4,1 | 14 | 45 | 3,4 | 3,40      |
| 0400   | BA-4 x 0,66 | 3,6 | 14 | 45 | 3,0 | 3,00      |
| 0500   | BA-5 x 0,59 | 3,2 | 14 | 45 | 3,0 | 2,60      |
| 0600   | BA-6 x 0,53 | 2,8 | 12 | 40 | 2,7 | 2,30      |
| 0700   | BA-7 x 0,48 | 2,5 | 10 | 40 | 2,1 | 2,00      |
| 0800   | BA-8 x 0,43 | 2,2 | 10 | 36 | 2,1 | 1,80      |

| Aceros<br>Carbono | Aceros<br>Aleados | Aceros<br>Preendurecidos | Aceros<br>Endurecidos |         | Fundición | Aluminio | Inoxidable | Titanio | Cobre | Bronce | CFRP |
|-------------------|-------------------|--------------------------|-----------------------|---------|-----------|----------|------------|---------|-------|--------|------|
| -HB225<br>◎       | HB225 -325        | HRc30-45                 | HRc 45 -55            | HRc 55- |           |          |            |         |       |        |      |