

ARANDELA PLANA

DIN 125



Para métrica	d	D	s	DIN 125 Sin baño	DIN 125 Zincada	DIN 125 Alta resistencia
M-3	3,2	7	0,5	•	•	
M-4	4,3	9	0,8	•	•	
M-5	5,3	10	1	•	•	
M-6	6,4	12	1,6	•	•	□
M-7	7,4	14	1,6	•	•	
M-8	8,4	16	1,6	•	•	□
M-10	10,5	20	2	•	•	□
M-12	13	24	2,5	•	•	□
M-14	15	28	2,5	•	•	□
M-16	17	30	3	•	•	□
M-18	19	34	3	•	•	□
M-20	21	37	3	•	•	□
M-22	23	39	3	•	•	□
M-24	25	44	4	•	•	□
M-27	28	50	4	•	•	□
M-30	31	56	4	•	•	□
M-33	34	60	5	•	□	
M-36	37	66	5	•	□	
M-39	40	72	6	•	□	
M-42	43	78	7	•	□	
M-45	46	85	7	•	□	
M-48	50	92	8	•	□	
M-52	54	98	8	•	□	
M-56	58	105	9	□	□	
M-60	62	110	9	□	□	
M-64	66	115	9	□		
M-68	70	120	10	□		
M-72	74	125	10	□		
M-76	78	135	10	□		
M-80	82	140	12	□		
M-90	93	160	12	□		
M-100	104	175	14	□		



• En stock

□ Consulten plazo de entrega

ARANDELA PLANA

DIN 125 INOXIDABLE AISI-304

Para métrica	d	D	h	DIN 125
M-3	3,2	7	0,5	•
M-4	4,3	9	0,8	•
M-5	5,3	10	1	•
M-6	6,4	12	1,6	•
M-8	8,4	16	1,6	•
M-10	10,5	20	2	•
M-12	13	24	2,5	•
M-14	15	28	2,5	•
M-16	17	30	3	•
M-18	19	34	3	•
M-20	21	37	3	•
M-22	23	39	3	•
M-24	25	44	4	•
M-27	28	50	4	•
M-30	31	56	4	•
M-33	34	60	5	□
M-36	37	66	5	□
M-39	40	72	6	□
M-42	43	78	7	□
M-45	46	85	7	□
M-48	50	92	8	□
M-50	52	92	8	□
M-52	54	98	8	□



• En stock

□ Consulten plazo de entrega